

Self-amalgamating tape - 3 meters roll length

To protect and prevent the antenna's connectors from oxidation and corrosion, this self-amalgamating tape is highly recommended to be use on our gateways.

Due to its silicone backing, the tape has an excellent resistance to various chemical substances, oils, acids, solvents, salt water, UV radiation and extreme temperatures.

No drying time is required. Its flexible material can be applied smoothly on any kind of surface, including wet or warm, dirty or oily.

Application: Stretch the tape to at least double its normal length. Apply it tight to all the connectors and overlap it tight onto itself.

We recommend to use 20cm for an antenna like the one in the picture beside.



Specifications

Material:	Silicon
Roll length:	3m
Roll width:	25mm
Total thickness:	500 µm
Elongation at break:	750 %
Tensile strength:	33 N/cm
Temperature resistance min.:	-60 °C
Temperature resistance max.:	+260 °C
Dielectric breakdown voltage:	8000 volts
Certified according to:	UL 510



Document Version: 0.1
Updated: June_the 15th

- Responsibility for the information and views set out in this document lies entirely with the manufacturer. Kerlink can't be held responsible for the exactness of information contained therein.
- Accessories are not covered by the maintenance nor warranty extension offers.
- The standard, legal manufacturer's warranty is 1 year.