

Wirnet™ iFemtoCell

LoRaWAN® Indoor Gateway for the Internet of Things



The “Wirnet™ iFemtoCell” is the ideal gateway to support your smart city, smart building or every smart project that requests dedicated indoor coverage and/or network densification, providing both a unique superior coverage and operational excellence.



Smart Energy



Smart Cities



Smart Agriculture
& Environment



Smart Building
& Facilities

Kerlink is certified ISO9001: 2015 by AFNOR certification. The Quality Management System gives high priority to Customer satisfaction and progress implementation.



Key Features

- Indoor LoRa® Gateway,
- Ingress protection (IP30),
- Supported unlicensed bands: 863-874.4MHz (EMEA, India), 902-928MHz (North America), 915-928MHz (APAC, Latin America),
- Supported LoRaWAN® regional parameters: EU863-870, IN865-867, RU864-870, US902-928, AU915-928, AS923, KR920-923,
- 8ch RX (125 kHz, multi Spreading Factor) + 1ch RX (250KHz or 500kHz, mono Spreading Factor) + 1ch RX (FSK) to get 10ch RX + 1ch TX,
- Backhaul connectivity: Wi-Fi 2.4GHz and Ethernet (RJ45) + 3G/4G external dongle (in option),
- Powered by:
 - Power supply (230VAC/12VDC) with provided jack connector 2.5mm/5.5mm,
 - Uninterrupted power supply with 24h autonomy (accessory),
- Highly secured device relying on a hardware secure core.

Key Differentiators

High performance, reliability & robustness

- Semtech Reference Design v1.5 components,
- Integrated Wi-Fi antenna,
- Built-in with high rejection filters.

Security HW and SW architecture

- SecureBoot (Signed firmware),
- SecureStorage (keys and certificates in secured area) using ProvenCore™ solution,
- Secured links and backhaul protection (OpenVPN/IPsec),
- Reboot (watchdog) and recovery to previous Management config (or factory config if the boot issue is not fixed).

All product specifications are subject to change without notice (V2.1)

Easy deployment

- Easy installation: Wall mounting by 2 oblong holes or lay on a table (4 domes),
- Easy access to connectivity:
 - Ethernet 10/100 Mbps (RJ45),
 - WPS push button,
 - 3 programmable LEDs,
 - 1 LED (green/red) for Power status,
 - 1 LED (green/red) for Backhaul status,
 - 1 LED (green/red) for LoRa® rf activity Rx/Tx,
- USB (Type A) connector for configuration,
- SMA or RP-SMA for LoRa® antenna,
- Reset button,
- Simple and convenient configuration, management, control and update via the Kerlink Wanesy™ Management Center (Alarm notifications, Firmware upgrade, platform statistics, RF statistics, RF spectrum analyzer...)
- Remotely configurable, manageable, via intuitive Web GUI,
- Remote access via SSH.

Technical Feature

- Sniffer for LBT (Listen Before Talk),
- Rx Sensitivity: -141 dBm (SF12),
- TX Conducted Power: configurable from 5dBm to 27dBm, LoRa® swivel antenna 3 dBi peak gain
- Range -20°C +55°C, (for gateway only, without power supply),
- Humidity: 5% to 95%,
- Size: 160 x 90 x 35 mm,
- Weight: 163g (Gateway only); 372g (with packing),
- Spectrum analysis compliant,
- Casing: IP30,
- CPU: ARM Cortex A9,
- DDRAM 256MB,
- 8GB eMMC (6GB available for user).

Value-added Services

- **Free access to Kerlink Wiki for customers**
- Plug & Play installation (option),
- Wirnet™ iFemtoCell is part of the end-to-end LoRa® connectivity solution with Kerlink Wanesy™ Management Center, remote monitoring and Operations Management suite (option),
- Wanesy™ SPN2 for Small Private Network, embedding a LoRa Network Server on the Gateway (option),
- Maintenance Services (option),
- **Kerlink Project Management:** a comprehensive service offering and a global network of specialist integrators to support your entire project.

Thanks to their expertise and experience, Kerlink teams are fully mobilized to help you develop your business and reduce your operational and commercial risks.

Don't hesitate to contact us:

Software Features

- **Same Software as Wirnet™ iBTS and iStation:** same user experience, quicker integration,
- **Dynamic web interface (On-the fly modifications),**
- **Programmable Gateway:** Toolchain, libraries and header files for compilation of homemade applications, or extra packages additions,
- **Including:**
 - Operating System: KerOS with embedded GNU/Linux based on Yocto 2.4 and LTS kernel 4.14,
 - Native Language Support: Python2, C/C++ and Shell,
 - Included packages: SQLite (Database), Connman/Ofono, NTPd, lighttpd.



Certifications

868	915	923
<ul style="list-style-type: none"> • Europe • Turkey • India 	<ul style="list-style-type: none"> • USA • Canada 	<ul style="list-style-type: none"> • Australia • New-Zealand • Singapore • Argentina • Brazil • Taiwan • South Korea • Japan • Hong-Kong • Malaysia • Indonesia • Vietnam • Thailand • Philippines

(For any specific need, please contact us)

Wirnet™ iFemtoCell - Ordering references

Product Ordering References

Reference	Designation	Description	ISM Frequencies
PDTIOT-IFE00	Wirnet iFemtocell 868 MHz	8CH LoRa, Indoor, Wifi backhaul + ETH backhaul	863-874.4MHz
PDTIOT-IFE01	Wirnet iFemtocell 915 MHz	8CH LoRa, Indoor, Wifi backhaul + ETH backhaul	902-928MHz
PDTIOT-IFE02	Wirnet iFemtocell 923 MHz	8CH LoRa, Indoor, Wifi backhaul + ETH backhaul	915-928MHz

All product specifications are subject to change without notice (V2.1)

868 Accessory Ordering References (Wirnet™ iFemtoCell)

Plug Cigarette Lighter		Description	Recommendation
KLK03371	Plug Cigarette Lighter		
UPS (Uninterruptible Power Supply)			
KLK03374	Nano UPS 5V-12V 6Ah		
ACCIOT-UPS00	Mini UPS 12V 7Ah	40W - DC/DC CONVERTER - 48VDC Input	
DEBUG			
ACCWM2-SDE00	Debug Probe	Wirnet iBTS / Wirma Debug Probe	

915 Accessory Ordering References (Wirnet™ iFemtoCell)

DEBUG			
ACCWM2-SDE00	Debug Probe	Wirnet iBTS / Wirma Debug Probe	

923 Accessory Ordering References (Wirnet™ iFemtoCell)

DEBUG			
ACCWM2-SDE00	Debug Probe	Wirnet iBTS / Wirma Debug Probe	