

Power supply cables

To power all our AC devices, we recommend to use our cords according to your country. Here our references for United States, United Kingdom, Australia and Japan.

United States:

Ordering number : KLK03555

Picture



This is a 1,83 meter AC power cord for North America, C13 for C14 inlet.

Specifications

Connector 1	NEMA 5-15P
Connector 2	C13
Cable Length (mm)	1830
Wire Gauge (AWG)	18
Wire Gauge (mm)	0.75
Cable Style	Round
Jacket Material	PVC
Shielding	No
Voltage Rating (Vac)	125
Current Rating (A)	10
Color	Black
Operating Temp Range (°C)	-20 ~ 105
Approvals	CE RoHS SAA UL

Document Version: v0.2
Updated: September the 30th

- Responsibility for the information and views set out in this document lies entirely with the manufacturer. Kerlink can't be held responsible for the exactness of information contained therein.
- Accessories are not covered by the maintenance nor warranty extension offers.
- The standard, legal manufacturer's warranty is 1 year.

United Kingdom:

Ordering number : KLK03554

Picture



This is a 1,83 meter AC power cord for UK, C13 for C14 inlet.

Specifications

Connector 1	BS1363A
Connector 2	C13
Cable Length (mm)	1830
Wire Gauge (AWG)	18
Wire Gauge (mm)	0.75
Cable Style	Round
Jacket Material	PVC
Shielding	No
Voltage Rating (Vac)	250
Current Rating (A)	10
Color	Black
Operating Temp Range (°C)	-15 ~ 70

Approvals



Australia:

Ordering number : KLK03553

Picture



This is a 1,83 meter AC power cord for Australia, C13 for C14 inlet.

Specifications

Connector 1	AS3112
Connector 2	C13
Cable Length (mm)	1830
Wire Gauge (AWG)	18
Wire Gauge (mm)	0.75
Cable Style	Round
Jacket Material	PVC
Shielding	No
Voltage Rating (Vac)	250
Current Rating (A)	10
Color	Black
Operating Temp Range (°C)	-15 ~ 70

Approvals



Japan:

Ordering number : KLK03055

Picture



This is a 1,83 meter AC power cord for Japan, C13 for C14 inlet.

Specifications

Connector 1	NEMA 5-15P
Connector 2	C13
Cable Length (mm)	1830
Wire Gauge (AWG)	18
Wire Gauge (mm)	0.75
Cable Style	Round
Jacket Material	PVC
Shielding	No
Voltage Rating (Vac)	125
Current Rating (A)	7
Color	Black
Operating Temp Range (°C)	-10 ~ 60
Approvals	CE ROHS JET